



339091

TAMER II INSTALLATION INSTRUCTIONS

FITS ALL SPORTSTER MODELS 1970 THRU 1983

1. Remove outer primary cover to expose clutch
2. Remove clutch pressure plate and spring using oem spring tool or large gear puller to compress clutch spring
3. Remove clutch plug center of bearing end replace it with our clutch plug
4. Main input gear in center of the clutch shell is to receive the bushing, insert it so chamfer is toward you
5. Put some grease in the bushing
6. Re-install pressure plate and spring, tighten the 6 nuts
7. Install outer primary cover and on later models adjust the primary chain
8. Adjust the clutch as described in the Harley manual
9. Add oil to primary. We recommend the use of Hawg/Revtech primary oil (ZPN 232004). With a good oil the clutch will work better



339091

TAMER II INSTALLATION INSTRUCTIONS

FITS ALL SPORTSTER MODELS 1970 THRU 1983

1. Remove outer primary cover to expose clutch
2. Remove clutch pressure plate and spring using oem spring tool or large gear puller to compress clutch spring
3. Remove clutch plug center of bearing end replace it with our clutch plug
4. Main input gear in center of the clutch shell is to receive the bushing, insert it so chamfer is toward you
5. Put some grease in the bushing
6. Re-install pressure plate and spring, tighten the 6 nuts
7. Install outer primary cover and on later models adjust the primary chain
8. Adjust the clutch as described in the Harley manual
9. Add oil to primary. We recommend the use of Hawg/Revtech primary oil (ZPN 232004). With a good oil the clutch will work better